


SV12-23 双向常开电磁阀 Bi-direction Open


订购型号 Order Type

SV12-23-①

①线圈电压：直流电压 (V) 12, 24
交流电压 (V) 110, 220



流量曲线 Performance (Cartridge Only)




特性 Features


- 断电时，液压油从②流向①，同时液压油也可从①到②；通电时，①到②开启。此模式容许双向流动。
- 用于控制流量 80 L/min 及压力达 250bar 之开启与关闭，典型应用控制液压系统之传动装置。
- 额定流量：80 L/min 最大压力：250bar
- 液压油自②至①泄漏：在210bar以及油粘稠度为46cSt时是0.10 ml/min (2滴)。
- 工作温度：
 - 最低-30℃，最高100℃，使用标准型BUNA衬垫。

- When de-energized, the poppet lifts to open from ② to ①, flow is also open from ① to ②. When energized, the cartridge acts as a check valve, allowing from ① to ②, while blocking flow ② to ①. In this mode, bidirectional flow is allowed.
- Valve open and close under the controlled flow of 80 L / min and pressures up to 250bar, a typical application of Hydraulic system gear.
- Operating flow rate: 80 L / min Operating Pressure: 250bar .
- Hydraulic oil leak from ② to ①: In the 210bar and oil viscosity for 46cSt when 0.10 ml / min (2 drops).
- Temperature:
 - 30 °C to 100 °C, with standard BUNA seals.

尺寸图 Dimensions



阀孔尺寸 VC122



未注公差：± 0.05